

MARK III SILENT TPS

Electric

MARK III SILENT
TPS 210 EM¹MARK III SILENT
TPS 235 ETMARK III SILENT
TPS 315 ETMARK III SILENT
TPS 380 ET

Charging rate	210 l/min	235 l/min	315 l/min	380 l/min
Filling time ²	10 min	8.30 min	6.20 min	5.15 min
Engine power	4 kW Three-phase electric	4 kW Three-phase electric	5,5 kW Three-phase electric	7,5 kW Three-phase electric
Dimensions ³ (L x D x H)	108 x 86,5 x 91,5 cm 42.5 x 34 x 36 in			
Weight ³ (dry weight)	181 kg 399 lb			191 kg 421 lb


¹ Data referred to the maximum pressure of 232 bar² Filling time 10 l empty cylinder - 0/200 bar (tolerance ±5%)³ Standard model. Weight and dimensions may vary depending on accessories.

No compromise

The **MARK III SILENT TPS** range is ideal for intensive use in hot, poorly ventilated environments or in tropical countries. Designed with an improved cooling system and a filtering system with two Hyperfilters, these compressors are powered by an electric motor and equipped with four different pumping units, all in TPS (Tropical Plus Superdry) version. They are available with function monitoring systems and electrical panel for automatic compressor shutdown.

Working pressure from 232 to 420 bar

Standard equipments



Optional



ERGO TPS

Electric



ERGO TPS 235 ET

ERGO TPS 270 EM¹

ERGO TPS 315 ET

Charging rate	235 l/min	270 l/min	315 l/min
Filling time ²	8.30 min	7.20 min	6.20 min
Engine power	4 kW Three-phase electric	5,5 kW Three-phase electric	5,5 kW Three-phase electric
Dimensions ³ (L x D x H)		112 × 63 × 77 cm 44.1 × 24.8 × 30.3 in	
Weight ³ (dry weight)	174 kg 384 lb		184 kg 406 lb

1 Data referred to the maximum pressure of 232 bar

2 Filling time 10 l empty cylinder - 0/200 bar (tolerance ±5%)


3 Standard model. Weight and dimensions may vary depending on accessories.

Less is more

ERGO TPS is the best solution for those who want a compact breathing air compressor without compromising on high performance. Equipped with four different TPS (Tropical Plus Superdry) pumping units, ERGO TPS is powered by electric motors or engines (Honda for the petrol version, Kohler for the diesel compressors). It has a panel with a monitoring system complete with pressure gauges, autostop with adjustable electronic pressure switch, automatic condensate drain and rotation direction control. It also has two connections for high pressure hoses and an improved filtering system with two Hyperfilters. The remote charging panel is available as an option.

Working pressure from 232 to 420 bar

Standard equipments



Optional



SUPER SILENT TPS

Electric



SUPER SILENT TPS 235 ET

SUPER SILENT TPS 315 ET

Charging rate	235 l/min	315 l/min
Filling time ¹	8.30 min	6.20 min
Engine power	4 kW Three-phase electric	5,5 kW Three-phase electric
Dimensions ² (L x D x H)	90 x 93 x 132 cm 35.4 x 36.6 x 52 in	
Weight ² (dry weight)	212 kg 467 lb	222 kg 489 lb

1 Filling time 10 l empty cylinder - 0/200 bar (tolerance ±5%)




2 Standard model. Weight and dimensions may vary depending on accessories.

Listen to its absolute silence

The **SUPER SILENT TPS** model is specifically designed to minimise noise. It features an enhanced cooling and sound insulation system and an efficient filtering system with two Hyperfilters. Powered by an electric motor, it has four different pumping units, all in the TPS (Tropical Plus Superdry) version, and an intuitive control panel. For longer filter life, we recommend the Tornado high pressure dryer.

Working pressure from 232 to 420 bar

Standard equipments



Optional

